

## SELECT FINE TEXTURE

### Product Description

Select Fine Texture is a general purpose water base fine texture coating based on a tough, flexible acrylate-copolymer resin, pigmented with titanium dioxide and other high grade alkali resisting pigments, reinforced with selected mineral aggregates. Its special formulation incorporating fungicides and algacides and its build ensures good weather resistance. It helps to cover hairline surface cracks and irregularities. Ideal as a decorative and protective coating.

### Recommended Areas of Application

**Area of Use:** Exterior and Interior

**Substrate:** Concrete, plaster, masonry, brickwork, blockwork, gypsum, timber.

### Technical Data

**Sheen Variants:** Fine Texture, Matt

**Colours:** As per shade card

**Volume Solids:** 50 ± 2%

Theoretical Covering Capacity		
Recommended Dry Film Thickness per coat		Theoretical Spread rate
<b>Minimum</b>	75 microns	6.6 m <sup>2</sup> /Ltr
<b>Maximum</b>	125 microns	4 m <sup>2</sup> /Ltr

Practical Covering Capacity
For estimation of practical covering capacity, following factors to be taken into account: surface profile, uneven application, over spray, losses container and equipment etc.

Drying time	Substrate Temp.	Touch Dry	Overcoating Interval	
			Minimum	Maximum
	25°C	2 hours	8 hours	Indefinite
	35°C	1.5 hours	6 hours	Indefinite
	45°C	1 hours	4 hours	Indefinite

### Application Data

**Method of Application** : Brush, Roller application.

**Thinner** : Sweet water

**Thinning Ratio (by vol.)** : Use 5% to 10% for ease of application. Dilution with sweet water. Over dilution will make the texture pattern smaller, lower opacity & shades may vary.

### Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

- Ensure surface is clean, dry and free from all contaminants.
- Surface must be sound and free from laitance.
- Remove laitance by wire brush or sweep blast.

Note: Fungal growth should be treated with Bison Fungicidal Solution.

### Application Details

- Ensure adequate ventilation during application and drying.
- Do not apply when humidity exceeds 85% and condensation is likely.
- Surface temperature should be 3°C or more above dew point.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using an upward lifting action.

**Roller:** Apply an even coat taking care to avoid runs and sags. Minimum two coats recommended.

**Brush:** May also be used for small areas. The type of texture will be different.

RECOMMENDED PAINT SYSTEM	
System 1	System 2
1 coat x Berger Acrylic A R Primer	1 coat x Value Primer Sealer
2 coats x Select Fine Texture	2 coats x Select Fine Texture

### Storage, Safety Information And Precautions

- Keep out of reach of children.
- Store in cool, dry conditions; ensure adequate ventilation during application.
- Avoid contact with skin and eyes; wear suitable protective clothing such as overalls, goggles, dust masks and gloves.

### First-Aid

- Eyes: In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- Skin: Wash skin thoroughly with soap and water, or with an approved industrial cleaner. Do not use solvents.
- Inhalation: Move patient to fresh air, loosen collar and keep patient rested.
- Ingestion: Do not induce vomiting. Obtain immediate medical attention.
- Shelf life up to 12 months.
- Dispose off Container / Paints as per applicable statutory regulations.

### Disclaimer

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the datasheet may be modified by us without notice.

*"This Technical Data Sheet supersedes those previously issued with immediate effect  
 For more information please contact us at: [customerservice.oman@asianpaints.com](mailto:customerservice.oman@asianpaints.com)"*