

ROYALE PLAY ITALIAN STUCCO

PRODUCT DESCRIPTION

Berger Italian Stucco is a top of the range water based venetian finish which creates attractive boundless marble-like effects on various surfaces. This product is a carefully engineered one to get the best of the skill of an applicator and imagination of an artist.

RECOMMENDED AREAS OF APPLICATION

Luxury range interior finish
For obtaining natural marble decoration respecting the ancient tradition
Unlimited marble effects
Hygienic and anti-fungal
It is possible to obtain a glossy or satin finish
Decorative effects to redefine surroundings
User and Eco-friendly
Dirt resistant and non-toxic

TECHNICAL DATA

Colours	: As per color card of custom-made color
Finish	: Smooth, Satin and Glossy
% Volume Solids	: 54 ± 2 %
Thinner/Cleaner	: Soft Water
Pack Sizes	: 1.4 Kg, 5 Kg, 14 Kg
Spreading Capacity	: Solely dependent on the surface profile and the extent of finish required. However, as a guideline only, 3.5 m ² may be considered for reasonably smooth plastered surface.
Drying time	: Thorough drying for 6 hours after application of final coat under ambient temperature of 35°C.

SURFACE PREPARATION

Ensure the surface is clean, dry & free from all loose or flaking particles. Apply the recommended primer for the substrate, followed by your choice of Berger Royale Matt basecoat, prior to application of Berger Italian Stucco.

SYSTEM RECOMMENDATION

- Berger Italian Stucco can be applied under normal conditions to add value to the conventional systems.
- On fresh plaster: 1 coat of Berger PVA Primer, 2 coats of Berger Decora Stucco, 1 coat of Berger Royale Matt Emulsion and finally apply Berger Italian Stucco.
 - On previously painted surface: Berger Royale Matt Coat followed by Berger Royale Play Italian Stucco.
 - On wooden surfaces: 1 coat of Berger Woodorite Primer, 1 coat of Universal Undercoat, Berger Royale Matt Emulsion and finally 1 coat of Berger Royale Play Italian Stucco for a smooth and polished finish one coat of polish recommended on top of stucco finish.

METHOD OF APPLICATION

- Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 85% and condensation is likely. Only apply coating when surface temperature is 3°C or more above dew point.
- This material is ready to use. Dilution with water is not recommended.
- Apply First coat of stucco wait 1-2 hours.
- After second coat, smooth the surface using the other color, wait 1-2 hours.
- Third coat if needed, to have the polished effect, sleeking the product with a metal spatula.

STORAGE, SAFETY INFORMATION AND PRECAUTIONS

STORAGE : Store in a cool dry shaded area.

SAFETY PRECAUTIONS : Ensure that there is adequate ventilation in the area where the product is being applied.
Do not breathe vapour or spray.

FIRST AID

Eyes : In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin : Wash skin thoroughly with soap and water or an approved industrial cleaner. DO NOT USE solvent or thinners.

Inhalation : Remove to fresh air, loosen collar and keep patient rested.

Ingestion : In case of accidental ingestion DO NOT INDUCE VOMITING. Obtain immediate medical attention.

DISCLAIMER

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the data sheet may be modified by us without notice.

*"This Technical Data Sheet supersedes those previously issued with immediate effect
For more information please contact us at: customerservice.oman@asianpaints.com"*