

ROYALE PLAY SAFARI

Product Description

Royale Play Safari is a water-based special effects paint that creates a variety of special effects on the interior walls. The product is inspired from fashion and glitters and helps bring these elements into home décor..

Recommended Areas of Application

Area of Use: Interior

Substrate: Concrete, plaster, Masonry, Gypsum, Timber.

Technical Data

Sheen Variants: Glitter with sheen

Colours: Available in various shades

Theoretical Covering Capacity: 5-10 m²/ltr per coat according to thinning, pattern, substrate, base coat, and style of painting

Capacity : Also based on desired effect

Pack Size : 1 Ltr, 4 Ltr

	Substrate Temp.	Touch Dry	Overcoating Interval	
			Maximum	Hard Dry
Drying time	25°C	3 hrs	8 hours	48 hours

Application Data

Method of application : Brush, Roller, Sea Sponge, Roller with special effects, Cloth, Rag, etc.

Thinner : Water

Thinning ratio (by vol.) : If necessary

Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

- Ensure surface is clean, dry and free from all contaminants.
- Surface must be sound and free from laitance.
- Remove laitance by wire brush or sweep blast.

Note: Fungal growth should be treated with Bison Fungicidal Solution. After drying, one coat of Plastaseal Penetrating Sealer should be applied.

Application Details

- Ensure adequate ventilation during application and drying.
- Do not apply when humidity exceeds 85% and condensation is likely.
- Surface temperature should be 3°C or more above dew point.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using an upward lifting action.

Use appropriate application tool depending on the design required to be created. It is suggested that a high quality application tool be used to ensure superior effects.

TYPICAL PAINT SYSTEM

1 coat x Berger Acrylic A R Primer

As required: Value Stucco

2 coats x Royale Silk Emulsion

Royale Play Metallics

Storage, Safety Information And Precautions

- Keep out of reach of children.
- Store in cool, dry conditions; ensure adequate ventilation during application.
- Avoid contact with skin and eyes; wear suitable protective clothing such as overalls, goggles, dust masks and gloves.

First-Aid

- Eyes: In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- Skin: Wash skin thoroughly with soap and water, or with an approved industrial cleaner. Do not use solvents.
- Inhalation: Move patient to fresh air, loosen collar and keep patient rested.
- Ingestion: Do not induce vomiting. Obtain immediate medical attention.
- Dispose in landfill only.

NB: The information reported in this technical data sheet comes from our best experience; however this does not involve any responsibility of our Company for applications of this product without our control.

Disclaimer

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the data sheet may be modified by us without notice.

*"This Technical Data Sheet supersedes those previously issued with immediate effect
 For more information please contact us at: "customerservice.oman@asianpaints.com"*

Version No APME/2018/01

Asian Paints (Middle East) LLC
 Ghala Industrial Area, Al - Khuwair
 Postal Code : 133, P.O Box :462
 Sultanate of Oman