

Technical Data Architecture Coatings

Royale Play Textile

Product Description

Royale Play Textile is a water-based special effects paint that creates a variety of special effects on the interior walls. The product is inspired from fashion and fabrics and helps bring these elements into home décor.

Recommended Areas of Application

Area of Use : Interior
Substrate : Concrete, Plaster, Masonry, Gypsum, Timber.

Technical Data

Sheen Variants : Low Sheen
Colours : Available in various shades using Colour World Tinting System.
Theoretical Covering Capacity : 15-20 m²/ltr per coat according to thinning, pattern, substrate, base coat, and style of painting. method of application and weather conditions.

Drying time	Substrate Temp.	Touch Dry	Overcoating Interval	
			Maximum	Hard Dry
	25°C	3 hours	12 hours	48 hours

Application Data

Method of application : Brush, roller, sea sponge, roller with special effects, cloth, rag, etc.
Thinner : Water
Thinning ratio (by vol.) : 50% or more, depending in the method of application, and desired effect. Although this product will appear thick after tinting, this is a special property for a crisp pattern, so do not over-dilute.

Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

- Ensure surface is clean, dry and free from all contaminants.
- Surface must be sound and free from laitance.
- Remove laitance by wire brush or sweep blast.

Note: Fungal growth should be treated with Bison Fungicidal Solution. After drying, one coat of Plastaseal Penetrating Sealer should be applied.

Application Details

- Ensure adequate ventilation during application and drying.
- Do not apply when humidity exceeds 85% and condensation is likely.
- Surface temperature should be 3°C or more above dew point.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using an upward lifting action.

Use appropriate application tool depending on the design required to be created. It is suggested that a high quality application tool be used to ensure superior effects.

TYPICAL PAINT SYSTEM

1 coat x AR Primer/PVA Primer Sealer/As recommended by the Company

As required: Value Stucco/Extra mix/Stucco/As recommended by the Company

2 coats x Royale Luxury Silk Emulsion

Royale Play Textile

Storage, Safety Information And Precautions

Storage and Handling:

- Keep out of reach of children.
- Store in cool, dry conditions; ensure adequate ventilation during application.
- Avoid contact with skin and eyes; wear suitable protective clothing such as overalls, goggles, dust masks and gloves.
- Shelf life up to 24 month is from the date of manufacture.

First-Aid

- Eyes : In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- Skin : Wash skin thoroughly with soap and water, or with an approved industrial cleaner. Do not use solvents.
- Inhalation : Move patient to fresh air, loosen collar and keep patient rested.
- Ingestion : Do not induce vomiting. Obtain immediate medical attention.
- Dispose in landfill only.

NB: The information reported in this technical data sheet comes from our best experience; however this does not involve any responsibility of our Company for applications of this product without our control.

Disclaimer

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the data sheet may be modified by us without notice.

This Technical Data Sheet supersedes those previously issued with immediate effect