

Technical Data Architecture Coatings

Royale Play Textile

Product Description

Royale Play Textile is a water-based special effects paint that creates a variety of special effects on the interior walls. The product is inspired from fashion and fabrics and helps bring these elements into home décor.

Recommended Areas of Application

Area of Use : Interior
Substrate : Concrete, Plaster, Masonry, Gypsum, Timber

Technical Data

Sheen Variants : Low Sheen
Colours : Available in various shade using colour world tinting system
Theoretical Spread rate : 15 - 20 m²/ltr per coat according to thinning, pattern, base coat, and style of painting
Practical Covering Capacity : For estimation of practical covering capacity, following factors to be taken into account surface profile, uneven application, overspray, losses in container and equipment etc.

Drying time	Substrate Temperature	Touch Dry	Hard Dry	Re coating Interval
				Maximum
	25°C	3 Hours	48 Hours	12 Hours

Application Data

Method of application : Brush, Roller, Sea Sponge, Roller with special effects, Cloth, Rag etc.
Thinner : Sweet water.
Thinning ratio (by vol.) : 50% or more, depending in the method of application, and desired effect. Although this product will appear thick after tinting, this is the special property for crisp pattern, so do not over-dilute.

Surface Preparation

- The performance of this coating is directly related to the degree of surface preparation.
- New concrete should be left for at least 28 days to cure before coating.
- Substrate should have sufficient strength to receive the paint. Any defects in the substrate like surface undulation, cracks, pin holes etc. should be rectified/ filled before starting painting. The compatibility of any third party filling material, if used, shall be confirmed with Berger before application.
- The surface must be clean and free from all loose extraneous materials such as loose paint, dust or loosely adhering concrete etc.
- If fungus or algae is present, first treat with Fungicidal Wash and leave for 24 Hours. Then, thoroughly rinse and wash or scrape away all the fungus.
- If grease or oil is present, clean using a mild detergent and rinse thoroughly to ensure complete removal of the grease and detergent.
- Do not apply paint when the surface is wet.

Application Details

- Ensure adequate ventilation during application and drying.
- Do not apply when humidity exceeds 85% and condensation is likely.
- Surface temperature should be 3°C or more above dew point.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using an upward lifting action.

Use appropriate application tool depending on the design required to be created. It is suggested that a high quality application tool be used to ensure superior effects.

Typical Paint System

1 coat x Acrylic A.R. Primer
As required: Value Stucco Putty
1 coat of Royale Luxury Silk.
Royale Play Textile

Storage, Safety Information And Precautions

Kindly refer to the Safety Data Sheet (MSDS) for further information on safety measures.

Storage : Store the container with the lid tightly closed in an upright position, in a cool, dry place, well ventilated space and keep away from sources of heat and ignition. Keep out of reach of children and away from eatables.

Shelf Life : Upto 12 months

Disposal : Left-over paint/drums should not be disposed in soil/drains. Consumers should consult a local recycling agency for proper disposal of paint/drums or dispose as per applicable statutory regulation.

Safety Precautions

- Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust masks and gloves. Use a barrier cream.
- Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe vapour or spray.

First Aid

Eyes : In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

Skin : Wash skin thoroughly with soap and water or an approved industrial cleaner. DO NOT USE solvent or thinners.

Inhalation : Remove to fresh air, loosen collar and keep patient rested.

Ingestion : In case of accidental ingestion, DO NOT INDUCE VOMITTING. Obtain immediate medical attention.

Disclaimer

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the data sheet may be modified by us without notice.

This Technical Data Sheet supersedes those previously issued with immediate effect