

# Technical Data Architecture Coatings

## Royale Play Solvent Glaze

### Product Description

Royale Play Glaze is a high quality translucent oil-based paint to be used as a topcoat for making designer finishes such as combing, ragging, colour wash, sponging etc.

### Recommended Areas of Application

**Area of Use** : Interior  
**Substrate** : Suitable Concrete, Plaster, Masonry, Gypsum, Timber

### Technical Data

**Sheen Variants** : Low Sheen  
**Colours** : Available in specific shades using Colour World Tinting System.  
**Shelf Life** : Upto 24 months from the date of manufacturing.  
**Theoretical Coverage** : 15 - 20 m<sup>2</sup>/ltr per coat depending on thinning, pattern, substrate, base coat, and style of painting.  
**Practical Coverage** : Practical coverage may depend on surface profile, method of application and weather conditions.

Drying time	Substrate Temp.	Touch Dry	Tack-free Dry
	40°C	6 hours	24 hours
	25°C	12 hours	48 hours

The drying time of this product will largely vary based on the type of the undercoat, pattern and shade chosen, extent and nature of the thinner, and ambient conditions like air circulation, temperature, humidity etc. The above drying times should be taken only as guideline for Glaze applied in a well ventilated room on a cured natural surface in one coat of minimum thickness.

### Application Data

**Method of application** : Brush, roller, sea sponge, roller with special effects, cloth, rag, etc.  
**Thinner** : Solvalux 7 – 9, 7 – 25  
**Thinning ratio (by vol.)** : Typically around 40% depending on the method of application, and desired effect.

## Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

- Ensure surface is clean, dry and free from all contaminants.
- Surface must be sound and free from laitance.
- Remove laitance by wire brush or sweep blast.

## Application Details

- Ensure adequate ventilation during application and drying.
- Do not apply when humidity exceeds 85% and condensation is likely.
- Surface temperature should be 3°C or more above dew point.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using an upward lifting action.

NOTE: Use appropriate application tool depending on the design required to be created. It is suggested that a high quality application tool be used to ensure superior effects.

### TYPICAL PAINT SYSTEM

1 coat x AR Primer/Value PVA Primer Sealer/As recommended by the Company

1 or 2 coats x Value Stucco/Extra Sealer mix/Stucco/As recommended by the Company

2 coats x Royale Luxury Silk Emulsion

Royale Play Glaze

For detailed system recommendation based on specific requirements please contact representative.

## Storage, Safety Information And Precautions

### Storage and Handling:

- Keep out of reach of children.
- Store in cool, dry conditions; ensure adequate ventilation during application.
- Avoid contact with skin and eyes; wear suitable protective clothing such as overalls, goggles, dust masks and gloves. Flash Point: 40°C.
- Dispose in landfill only.

### First-Aid

- Eyes : In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- Skin : Wash skin thoroughly with soap and water, or with an approved industrial cleaner. Do not use solvents.
- Inhalation : Move patient to fresh air, loosen collar and keep patient rested.
- Ingestion : Do not induce vomiting. Obtain immediate medical attention.

NB: The information reported in this technical data sheet comes from our best experience; however this does not involve any responsibility of our Company for applications of this product without our control.

## Disclaimer

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the data sheet may be modified by us without notice.

*This Technical Data Sheet supersedes those previously issued with immediate effect*