

# Technical Data Architecture Coatings

## Select Heavy Texture (WMC)

### Product Description

A heavy texture coating based on a tough, flexible acrylic co-polymer resin, pigmented with titanium dioxide and other light fast pigments reinforced with selected mineral quartz, mica and marble chips. Its formulation incorporating fungicides and algacides, and its heavy build ensures good weather resistance, and also helps cover hairline surface cracks and irregularities. helps cover hairline surface cracks and irregularities.

### Recommended Areas of Application

**Area of use** : Interior and Exterior  
**Substrate** : Concrete, Plaster, Masonry, Brickwork, Block work, Timber.

### Technical Data

**Sheen Variants** : Heavy Texture, Matt  
**Colours** : As per shade card  
**Volume Solids** : 68 ± 2%

Theoretical Covering Capacity	Recommended Dry Film Thickness per coat
	1.5 – 2.0 m <sup>2</sup> /ltr. Depending on surface profile, uneven application, type of texture pattern, losses in containers and equipment.

**Practical Covering Capacity** : For estimation of practical covering capacity, following factors to be taken into account: surface profile, uneven application, over spray, losses in container and equipment etc.

Drying time	Substrate temp.	Touch dry	Overcoating Interval	
			Minimum	Maximum
	25 °c	5 hours	12 hours	Indefinite
	35 °c	3 hours	8 hours	
	45 °c	2 hours	6 hours	

## Application Data

**Method of application** : Brush, Roller application.

**Thinner** : Sweet water

**Thinning ratio (by vol.)** : Use 5% to 10% for ease of application. Dilution with sweet water will make the textures smaller. Do not over dilute.

## Surface Preparation

The performance of this coating is directly related to the degree of surface preparation.

- Ensure surface is clean, dry and free from all contaminants.
- Surface must be sound and free from laitance.
- Remove laitance by wire brush or sweep blast.

Note: Fungal growth should be treated with Fungicidal Solution. After drying, one coat of Plastaseal Penetrating Sealer can be applied if required.

## Applications Details

- Ensure adequate ventilation during application and drying.
- Do not apply when humidity exceeds 85% and condensation is likely.
- Surface temperature should be 3°C or more above dew point.
- Stir the contents thoroughly before and during use, with a broad flat stirrer, using an upward lifting action.

**Roller** - Recommended. Apply an even coat taking care to avoid runs and sags. Minimum two coats recommended.

**Brush** - May also be used for small areas. The type of textures will be different.

### TYPICAL PAINT SYSTEM

#### Interior/Exterior

1 coat x AR Primer/Tuff AR Primer/WC AR Primer/As recommended by the Company

2 coats x Select Heavy Texture (WMC)/As recommended by the Company

For alternate system suggestion please contact Sales Representative

## Storage, Safety Information And Precautions

- Keep out of reach of children.
- Store in cool, dry conditions; ensure adequate ventilation during application.
- Avoid contact with skin and eyes; wear suitable protective clothing such as overalls, goggles, dust masks and gloves.
- Shelf life up to 24 month is from the date of manufacture.

#### First-Aid

- Eyes: In the event of accidental splashes, flush eyes immediately with warm water and obtain medical advice.
- Skin: Wash skin thoroughly with soap and water, or with an approved industrial cleaner. Do not use solvents.
- Inhalation: Move patient to fresh air, loosen collar and keep patient rested.
- Ingestion: Do not induce vomiting. Obtain immediate medical attention.
- Dispose in landfill only.

## Disclaimer

The information provided in this data sheet is not intended to be complete. It is the responsibility of the user to ensure that the product used is suitable for the purpose it is meant to serve. In view of various factors affecting the performance of the coating, we cannot assume responsibility for the product performance, nor do we accept any liability arising from use of this product, unless specifically agreed to in writing by us. The information provided in the data sheet may be modified by us without notice.

*This Technical Data Sheet supersedes those previously issued with immediate effect*